

INSTALLATION INSTRUCTIONS

BOLT-ON TOW HITCH

64-68 FORD ½ ton

PART# 2177147

For best results, please read all instructions thoroughly prior to attempting installation of your SIR MICHAEL'S products. SIR MICHAEL'S recommends the use of approved hand, eye and ear safety equipment while performing this installation. If you have any questions concerning the installation of your SIR MICHAEL'S steel roll pan, please contact our customer service department at (714) 379-6800, Monday through Friday between the hours of 8:00 a.m. and 4:00 p.m. Pacific Standard Time (PST).

NOTE: Any part that is modified and/or painted is non returnable.

1. All Sir Michaels tow hitches are designed to fit behind Sir Michaels steel roll pans, although some hitches will work with other manufacturers' roll pans.
2. This hitch will bolt to the factory holes on each side of the frame.
3. Install the hitch from the bottom, up to the frame using the grade 8 hard ware supplied. Your hitch will bolt to the bottom side of the frame rails.

Once all bolts are installed, tighten them down to the factory specs. Your hitch can now be accessed behind the license plate with a license plate flip, sold separately.

4. Sir Michaels does not supply a hitch wire plug and tow receiver due to the many different connections and drops. Most trailer and auto parts will carry those items.

Note: This hitch is not designed for use with lifted trucks or with use of drop receivers larger than a four inch drop. Use of larger drop receiver will void warranty.